55" ANDROID DOUBLED-SIDED FREESTANDING DIGITAL POSTER



Plug and Play

These displays have two separate built in HD Android media players and require no additional hardware or software. Load your pictures and videos onto a USB stick and insert it into one of the USB ports, this copies the files to the screen's internal memory. Once you remove the USB stick your pictures and videos will play in a continuous loop. It couldn't be simpler to get your content onto the screens.

Android Media Player

With a built in Android media players, these screens are more easily updateable and faster than ever before. The Android PC boards makes it easy to upgrade your screen to be networked and also allows you to run 3rd party Digital Signage software.

Free Scheduling Software

To get the most out of the screen, advanced users can use our free scheduling software that allows you to display different content at certain times of the day. You can also set image duration and transition effects using this software.

Eco Friendly Power Timer

This allows for reduced power usage by automatically powering off in hours that the displays are not required. You can set daily, or weekly, On/Off times for your displays.

24/7 Commercial Use

Commercial grade panels, with a lifespan of 50,000 hours, and high quality components ensure that these displays can be in constant use 24/7. Tablet-like styling is achieved thanks to their tempered glass front and robust steel enclosure.

LED Backlight Technology

The LED backlights built into these displays ensure improved brightness and contrast as well as drastically improving their lifespan and reducing their power consumption by around 30%. This form of light technology is mercury free; safeguarding this screen's eco friendliness.

Make Twice The Impact

This product exclusively features two screens that allow for the widest possible audience to see your content. With additional one sided or doubled sided touch screen upgrades you will never fail to leave an impression.


Internal Locker

If you need to run the screen from an external source, like a PC, you can do so by using the HDMI or VGA inputs. There is a space to fit a small PC inside the lockable compartment.

++4 (0)8450 944954 | hello@eclipsedigitalmedia.co.uk | Eclipse Digital Media, Unit L, Linsford Business Park, Linsford Lane, Mytchett, Surrey, GU16 6DJ

Technical Drawing

eclipse digital





USB -

\ USB



Specification

Panel Display Size 55 Inch Resolution 000000000000000000000000000000000000				
Panel Display Area (m) Image: Figure Figur	Panel	Display Size		55 Inch
Aspect Ratio Indianal sector (Amb) Brightness (cd/m2) 0 Colour 0 Viewing Angle 0 Contrast Raio 0 Audio Speaker Type 0 Power Power Construct Type 0 Input Voltage No 0 Power Power Construct Type 0 Power No 0 0 Forbitt (Wx) Video (MPG, AVI, MP4, RM, RMVE, TS), Audio (MP3, WMA), Inage (JPG, GIF, BMP, PNG) Media Formatis V		Resolution		1080x1920
Panel Brightness (cd/m2) Indextext (add/m2) Colour 16.7M Colour 18.7M 18.7M Contrast Ratio 4000.1 4000.1 Audio Speaker Type 9.400.0 Audio Speaker Type 9.400.0 Audio Vileo 4.00.1 Audio Vileo 9.400.0 Audio Vileo 0.400.0 Power Input Voltage 9.400.0 Input Voltage 0.400.0 2.500 Input Voltage (W+tx) mm) 0.400.0 2.600.0 Indi Size (W+tx) mm) 0.400.0 3.83.1379.138 Gross Weight (k) 0.400.0 1.920.180.100.0 Net Weight (k) 0.400.000.000.000.000.000.000.000.000.0		Display Area (mm)		682.4x1211.6
Brightness (cd/m2) Indextination (cd/m2) Colour Colour Viewing Angle Contrast Ratio Av Inputs Speaker Type Av Inputs Yideo Power Power (Colons) Power Power (Colons) Power Power (Colons) Power (Colons) Power (Colons) Power (Colons) Power (Colons) Power (Colons) Power (Colons) Power (Colons) Power (Colons) Power (Colons) Power (Colons) Power (Colons) Power (Colons) Power (Colons) Power (Colons) Power (Colons) Power (Colons) Power (Colons) Power (Colons) Power (Colons) Power (Colons) Power (Media Power) Power (Media Power) <		Aspect Ratio		16:9
Yeiving Angle Yeiving Angle Yeiving Angle Contrast Ratio Contrast Ratio 4000.1 Audio Speaker Type Generat Ratio A lindio Speaker Type Generat Ratio Aution Power Consumer Generation Power Power Consumer Generation Power Power Consumer Generation Power Onit Size (Witku Witku Withit) Generation Power Power Consumer Generation Power Power Generation Power Power Generation Generation Power Power Media Power Generation Power Media Power Video (MPG, AVI, MP4, RM, RMVB, RMVA, Jinage (JPG, GIF, BMP, PMG) Power Media Resolution Geneation<		Brightness (cd/m2)		450
Audio Speaker Type 4000.1 Audio Speaker Type 2W, 40 (x2) AV Inputs Yideo HDMI, VGA Audio Audio Sove Consumption (W) Gather Consumption (W) Power Input Voltage Addio Socket (3.5mm) Power Input Voltage (WxHxD mm) Sd 3x1979x138 Package Size (WxHxD mm) Sd 3x343.2x135 Footprint (WxD) Sd 3x343.2x450 Power 152 Working Tempert O 'C to 50 'C Working Tempert O 'C to 50 'C Working Tempert Video (MPG, AVI, MP4, RM, RMVB, TS), Audio (MP3, WMA), Image (JPG, GIF, BMP, PNG) Media Formats Video (MPG, AVI, MP4, RM, RMVB, TS), Audio (MP3, WMA), Image (JPG, GIF, BMP, PNG) Internal Memory GCPU Quad-Core Cortex-A17(0).161Hz GPU Guad-Core Cortex-A17(0).161GHz GPU IsB USB USB QUBB USB USB QUBB GB DDR3 Group terrint Memory GB DDR3 GB DDR3 IsB USB USB QUBB GB DDR3 IsB USB <td colspan="2">Colour</td> <td>16.7M</td>		Colour		16.7M
Audio Speaker Type End (%) AV Inpute Video HDM, VGA Audio Audio Socket (3.5mm) Power Power Consumption (W) Galdation (%) Input Voltage Voltage Galdation (%) Power Consumption (W) Galdation (%) Galdation (%) Power Consumption (%) Galdation (%) Galdation (%) Footprint (%) Galdation (%) Galdation (%) Footprint (%) Galdation (%) Galdation (%) Footprint (%) Galdation (%) Galdation (%) Row (%) Galdation (%) Galdation (%) Internal Media (%) </td <td colspan="2">Viewing Angle</td> <td>178°</td>		Viewing Angle		178°
AV Inputs Video Method Av Inputs Audio Audio Audio Audio Power Consumption (W) Audio Socket (3.5mm) Power Input Voltage AC110~240V (50Hz~60Hz) Input Voltage AC110~240V (50Hz~60Hz) AC110~240V (50Hz~60Hz) Mechanical Package Size (WxHxD mm) B43x1979x138 Package Size (WxHxD mm) B43x1979x138 B43x450 Power Footprint (WxD B43z430 Net Weight (kg) 0 °C to 50 °C B43z4450 Working Temperature 0 °C to 50 °C Computer Working Temperature 0 °C to 50 °C COU Working Temperature Video (MPG, AVI, MP4, RM, RMVE, TS), Audio (MP3, WMA), Image (JPG, GIF, BMP, PNG) Media Formats Video (MPG, AVI, MP4, RM, RMVE, TS), Audio (MP3, WMA), Image (JPG, GIF, BMP, PNG) Internal Memory G6B CPU Computer RAM COB Player RAM COB ROM USB 2.0 HOST (x2) LAN USB USB USB 2.0 HOST (x2) ViFi B0211b		Contrast Ratio		4000:1
AV inputs Audio Audio Power Power Consumption (W) 0 Input Voltage AC110~240V (50Hz~60Hz) Input Voltage Unit Size (WxHxD mm) 0 Package Size (WxHxD mm) 0 843x1979x138 Package Size (WxHxD mm) 0 1983x843_2x135 Footprint (WxD) 0 0 843.2x450 Net Weight (kg) 0 131 0 Gross Weight (kg) 0 0 0 °C to 50 °C Working Temperture Video (MPG, AVI, MP4, RM, RMVB, TS), Audio (MP3, WMA), Image (JPG, GIF, BMP, PNG) Internal Memory 6GB 0 0 Internal Memory GGB GPU GPU GPU UNB USB 20 HOST (x2) GPU GPU GBB NAND USB USB 20 HOST (x2) LAN 10/100M Ethernet (Network Version Only) UNF Fi Group Core Cortex -A17@1.61GHz Group Core Cortex -A17@1.61GHz GPU Madit - Tr50 MP4 @600MHz LAN LAN USB 20 HOST (x2) GR GR GR	Audio	Speaker Type		2W, 4Ω (x2)
Audio Vote Consumption (W) Input Voltage Power Consumption (W) AC110-240V (50Hz~60Hz) Input Voltage Size (WxHxD mm) AA110-240V (50Hz~60Hz) Package Size (WxHxD mm) 84331979x138 Package Size (WxHxD mm) 84332x450 Footprint (WxD) 8432.x450 Net Weight (kg) 152 Gross Weight (kg) 0°C to 50 °C Working Temperature Video (MPG, AVI, MP4, RM, RMVB, TS), Audio (MP3, WMA), Image (JP6, GIF, BMP, PNG) Media Formats Video (MPG, AVI, MP4, RM, RMVB, TS), Audio (MP3, WMA), Image (JP6, GIF, BMP, PNG) Media Formats Video (MPG, AVI, MP4, RM, RMVB, TS), Audio (MP3, WMA), Image (JP6, GIF, BMP, PNG) Media Formats Video (MPG, AVI, MP4, RM, RMVB, TS), Audio (MP3, WMA), Image (JP6, GIF, BMP, PNG) Internal Media Resolution 6GB Flauer RAM 2GB DDR3 ROM Ges USB UBOS USB USB UBOS USB UBOS USB USB USB UBOS Graphic Engine OpenGL ES 1.1/2.0/3.0/3.	AV Inputs	Video		HDMI, VGA
Power Input Voltage AC110-240V (50Hz-60Hz) Input Voltage Not Size (WXHXD mm) 843x1979x138 Package Size (WXHXD mm) 1983x843.2x135 Pootprint (WxD) 0 843.2x450 Net Weight (kg) 0 843.2x450 Korking Temperative 0 0°C to 50 °C Working Temperative Video (MPG, AVI, MP4, RM, RMVB, TS), Audio (MP3, WMA), Image (JPG, GIF, BMP, PNG) Internal Media Media Resolution 1920x1080/1080x1920 Internal Media RAM 2GB DDR3 ROM GBB NAND USB USB USB USB ColoST (X2) Vi F		Audio		Audio Socket (3.5mm)
Input Voltage Input Voltage AC110-240V (50H260H2) Unit Size (MxHxD mm) G 843x1979x138 Package Size (WxHxD mm) G 843x2x450 Footprint (WxD) G 843x2x450 Net Weight (kg) G 131 Gross Weight (kg) G 0 °C to 50 °C Working Temper Media Formats Video (MPG, AVI, MP4, RM, RMVB, TS), Audio (MP3, WMA), Image (JPG, GIF, BMP, PNG) Internal Media Media Resolution 1920x1080v1080x1920 Internal Media RAM CPU GPU Quad-Core Cortex-A17@1.61GHz GPU CPU Quad-Score Cortex-A17@1.61GHz Internal Media RAM 2GB DDR3 INERNA SB SGB NAND VISB USB USB OUSS2.0 HOST (x2) IAN 10/1000 Ethernet (Network Version Only) Wi-Fi 802.11b/g/n/ac (Network Version Only) Wi-Fi OpenGL ES 1.1/2.0/3.0/3.1, OpenCL 1.1, Renderscript, Direct3D 11.1 Special Video Scheduling Software, Remote Control, Key, User Manual	Power	Power Consumption (W)		250
Package Size (₩JD mm) Internal Media Fortprit (₩JD) Internal Media Netweight (№JD) Internal Media Netweight (№JD) Internal Media Netweight (№JD) Internal Media Internal Media Internal Media Player Internal Media Netweight (№JD) Internal Media Internal Media Internal Media Player Internal Media Internal Media Internal Media Internal Media Internal Media Internal Media Internal Media Internal Media Internal Media Internal Internal Media Internal Media		Input Voltage		AC110~240V (50Hz~60Hz)
Fortprint (WXD) Fortprint (WXD) Net Weight (kg) Gross Weight (kg) Gross Weight (kg) Working Temp=/ Working Temp=/ Media Formats Video (MPG, AVI, MP4, RM, RMVB, TS), Audio (MP3, WMA), Image (JPG, GIF, BMP, PNG) Media Resolution Internal Memory GPU Quad-Core Cortex-A17@1.61GHz GPU Quad-Core Cortex-A17@1.61GHz RAM ROM ViBB ROM ViBB USB ViBit	Mechanical	Unit Size (WxHxD mm)		843x1979x138
Mechanical Net Weight (kg) Image: Net Weight (kg) Image: Net Weight (kg) Gross Weight (kg) Media Formats 0 °C to 50 °C Working Temperator Media Formats Video (MPG, AVI, MP4, RM, RMVB, TS), Audio (MP3, WMA), Image (JPG, GIF, BMP, PNG) Media Formats Media Resolution 1920x1080/1080x1920 Internal Memory GGB 101 Player RAM GOuad-Core Cortex-A17@1.61GHz GPU Quad-Core Cortex-A17@1.61GHz BRM CPU GBB DDR3 RAM GBB DDR3 BRM USB2.0 HOST (x2) Internal Media Not View Media View GGB DDR3 BRM GOS Internal Media Not Player RAM GoS GOS Modia GOS GoS GOS GoS Gos Gos GOS Gos GOS Gos Android 51.1 Graphic Engine OpenGL ES1 1/2.0/3.0/3.1, OpenC1 1.1, Renderscript,		Package Size (WxHxD mm)		1983x843.2x135
Net Weight (kg) Image: Net Weight (kg) Image: Net Weight (kg) Gross Weight (kg) 0 °C to 50 °C Working Temperature 0 °C to 50 °C Working Temperature 0 °C to 50 °C Media Formats Video (MPG, AVI, MP4, RM, RMVB, TS), Audio (MP3, WMA), Image (JPG, GIF, BMP, PNG) Media Resolution 1920x1080/1080x1920 Internal Media Media Resolution Internal Media GPU RAM COBDR3 ROM GB DDR3 ROM GB DDR3 ROM USB2.0 HOST (x2) LAN 10/100M Ethernet (Network Version Only) Vi-Fi 802.11b/g/n/ac (Network Version Only) OS Android 5.1.1 Graphic Engine OpenGL ES 1.1/2.0/3.0/3.1, OpenCL 1.1, Renderscript, Direct3D 11.1 Special Inluded Scheduling Software, Remote Control, Key, User Manual		Footprint (WxD)		843.2x450
Working Temperative 0 °C to 50 °C Working Temperative Media Formats Video (MPG, AVI, MP4, RM, RMVB, TS), Audio (MP3, WMA), Image (JPG, GIF, BMP, PNG) Media Resolution 1920x1080/1080x1920 Internal Memory 6GB CPU Quad-Core Cortex-A17@1.61GHz GPU Media Pasoution RAM 2GB DDR3 ROM GBB Quad-Core Cortex-A17@1.61GHz USB USB2.0 HOST (x2) LAN USB2.0 HOST (x2) LAN 10/100M Ethernet (Network Version Only) Wi-Fi Gos Android 5.1.1 Os Android 5.1.1 Os Android 5.1.1 Special Images, Videos, Audio, Scrolling Text Message, On/Off Timer, On Screen Clock, Media Rotation Scheduling Software, Remote Control, Key, User Manual Scheduling Software, Remote Control, Key, User Manual		Net Weight (kg)		131
Media Formats Video (MPG, AVI, MP4, RM, RMVB, TS), Audio (MP3, WMA), Image (JPG, GIF, BMP, PNG) Media Resolution 1920x1080/1080x1920 Internal Memory 6GB CPU Cuad-Core Cortex-A17@1.61GHz GPU Mali-T760 MP4 @600MHz RAM 2GB DDR3 ROM USB USB USB2.0 HOST (x2) LAN 10/100M Ethernet (Network Version Only) Wi-Fi 802.11b/g/n/ac (Network Version Only) OS OpenGL ES 1.1/2.0/3.0/3.1, OpenCL 1.1, Renderscript, Direct3D 11.1 Special Images, Videos, Audio, Scrolling Text Message, On/Off Timer, On Screen Clock, Media Rotation Scheduling Software, Remote Control, Key, User Manual Scheduling Software, Remote Control, Key, User Manual		Gross Weight (kg)		152
Computer Media Resolution 1920x1080/1080x1920 Internal Media Internal Memory 6GB CPU Quad-Core Cortex-A17@1.61GHz GPU Media Resolution Player RAM 2GB DDR3 ROM USB USB2.0 HOST (x2) LAN 10/100M Ethernet (Network Version Only) Wi-Fi 802.11b/g/n/ac (Network Version Only) Wi-Fi 0penGL ES 1.1/2.0/3.0/3.1, OpenCL 1.1, Renderscript, Direct3D 11.1 Special Included Included Included Scheduling Software, Remote Control, Key, User Manual		Working Temperature		0 °C to 50 °C
Computer Internal Media Internal Memory 6GB Player CPU Quad-Core Cortex-A17@1.61GHz Player RAM Quad-Core Cortex-A17@0.01GHz RAM GPU Mali-T760 MP4 @600MHz Internal Media RAM 2GB DDR3 ROM USB USB2.0 HOST (x2) LAN 10/100M Ethernet (Network Version Only) Vi-Fi 802.11b/g/n/ac (Network Version Only) OS OpenGL ES 1.1/2.0/3.0/3.1, OpenCL 1.1, Renderscript, Direct3D 11.1 Special Images, Videos, Audio, Scrolling Text Message, On/Off Timer, On Screen Clock, Media Rotation Accessories Included Scheduling Software, Remote Control, Key, User Manual	Computer		Media Formats	Video (MPG, AVI, MP4, RM, RMVB, TS), Audio (MP3, WMA), Image (JPG, GIF, BMP, PNG)
Computer Internal Media Player CPU Quad-Core Cortex-A17@1.61GHz GPU Mali-T760 MP4 @600MHz BRM 2GB DDR3 ROM SGB NAND USB USB2.0 HOST (x2) LAN 10/100M Ethernet (Network Version Only) Wi-Fi 802.11b/g/n/ac (Network Version Only) OS Android 5.1.1 Graphic Engine OpenGL ES 1.1/2.0/3.0/3.1, OpenCL 1.1, Renderscript, Direct3D 11.1 Special Images, Videos, Audio, Scrolling Text Message, On/Off Timer, On Screen Clock, Media Rotation Accessories Included Scheduling Software, Remote Control, Key, User Manual			Media Resolution	1920x1080/1080x1920
Computer GPU Maii-T760 MP4 @600MHz Player RAM 2GB DDR3 ROM 8GB NAND USB USB2.0 HOST (x2) LAN 10/100M Ethernet (Network Version Only) Wi-Fi 802.11b/g/n/ac (Network Version Only) OS Graphic Engine OpenGL ES 1.1/2.0/3.0/3.1, OpenCL 1.1, Renderscript, Direct3D 11.1 Special Images, Videos, Audio, Scrolling Text Message, On/Off Timer, On Screen Clock, Media Rotation Accessories Included Scheduling Software, Remote Control, Key, User Manual			Internal Memory	6GB
Remain Media Player RAM 2GB DDR3 ROM ROM 8GB NAND USB USB USB2.0 HOST (x2) LAN 10/100M Ethernet (Network Version Only) Wi-Fi 0S RAM OpenGL ES 1.1/2.0/3.0/3.1, OpenCL 1.1, Renderscript, Direct3D 11.1 1 Special Images, Videos, Audio, Scrolling Text Message, On/Off Timer, On Screen Clock, Media Rotation Accessories Included Scheduling Software, Remote Control, Key, User Manual			CPU	Quad-Core Cortex-A17@1.61GHz
Computer ROM RO			GPU	Mali-T760 MP4 @600MHz
Accessories Included Included Included Included Included			RAM	2GB DDR3
Accessories Included LAN 10/100M Ethernet (Network Version Only) LAN 10/100M Ethernet (Network Version Only) Wi-Fi 802.11b/g/n/ac (Network Version Only) OS Android 5.1.1 Graphic Engine OpenGL ES 1.1/2.0/3.0/3.1, OpenCL 1.1, Renderscript, Direct3D 11.1 Included Images, Videos, Audio, Scrolling Text Message, On/Off Timer, On Screen Clock, Media Rotation			ROM	8GB NAND
Mi-Fi 802.11b/g/n/ac (Network Version Only) OS Android 5.1.1 Graphic Engine OpenGL ES 1.1/2.0/3.0/3.1, OpenCL 1.1, Renderscript, Direct3D 11.1 Special Images, Videos, Audio, Scrolling Text Message, On/Off Timer, On Screen Clock, Media Rotation Accessories Included			USB	USB2.0 HOST (x2)
OS Android 5.1.1 Graphic Engine OpenGL ES 1.1/2.0/3.0/3.1, OpenCL 1.1, Renderscript, Direct3D 11.1 Special Images, Videos, Audio, Scrolling Text Message, On/Off Timer, On Screen Clock, Media Rotation Accessories Included			LAN	10/100M Ethernet (Network Version Only)
Accessories Included			Wi-Fi	802.11b/g/n/ac (Network Version Only)
Special Images, Videos, Audio, Scrolling Text Message, On/Off Timer, On Screen Clock, Media Rotation Accessories Included Scheduling Software, Remote Control, Key, User Manual			OS	Android 5.1.1
Accessories Included Scheduling Software, Remote Control, Key, User Manual		Graphic Engine		OpenGL ES 1.1/2.0/3.0/3.1, OpenCL 1.1, Renderscript, Direct3D 11.1
Accessories		Special		Images, Videos, Audio, Scrolling Text Message, On/Off Timer, On Screen Clock, Media Rotation
Optional Network Upgrade, One Side Touch Screen Upgrade, Double Sided Touch Screen Upgrade	Accessories	Included		Scheduling Software, Remote Control, Key, User Manual
		Optional		Network Upgrade, One Side Touch Screen Upgrade, Double Sided Touch Screen Upgrade

+44 (0)8450 944954 | hello@eclipsedigitalmedia.co.uk | Eclipse Digital Media, Unit L , Linsford Business Park, Linsford Lane, Mytchett, Surrey, GU16 6DJ